

## Model 7063 FB6



### Use

Model 7063 comes ready for mounting as a complete window unit including hatch model 63.01 FB6. The unit is particularly suitable for use as a counter in indoor and outdoor areas. This model can be used in places such as the reception or front-desk counter in courthouses, embassies and correctional facilities.

### Safety and features

- Window unit with sliding pass-through for use as a flush-fitting pedestrian counter with front fascia and integrated Public intercom for automatic two-way conversation.
- Model 7063, front unit with pass-through, for interior and exterior use with everyday objects and documents up to 40 mm high (e.g. passes, files up to DIN A4 in size)
- Acrylic glass cover and drawer features a mechanical alternating automatic lock - the drawer can only be moved with the cover closed.
- Automatic lock at full extension in either direction. Lock can only be released by the operator behind the counter by using the lever.
- It is not possible to reach through the hole when the drawer is extended or manipulate the mechanism.

### Materials and use

- Safety glass adhering to BR6 NS.
- Unit made out of security steel and steel plate.
- Armouring and additional plates made out of armor steel
- Cover panel, compartment floor, cover and inner casing made of brushed stainless steel.
- All metal parts have been produced using state-of-the-art precision laser cutting technology for ultimate quality.
- Model 7063 is suitable for use in indoor and covered outdoor areas.
- The unit requires no maintenance. No need for cleaning or lubrication.

**Outer dimensions (all measurements in mm)**

Width 1090

Height 1280

Depth 591

**Drawer clearance**

Width 330

Depth 340

Height 40

Extension 300

**Mounting, wall recess**

1050 x 1200 (W x H)

**Weight**

300 kg

**Miscellaneous**

- Optional: fire-retardant up to F90
- Also available with window shutters and illumination.
- Special sizes available on request (excludes drawer).
- Frame coatings available in alternative RAL colours on request.

**Model 7063 FB6****Installation and dimensions**

The unit comes complete with power cables and is ready for exact mounting in prepared wall sections. It is inserted into the recess from the outside to fit flush with the wall. This is done by removing the inner frame before screwing the unit into place from the inside to prevent tampering. Consideration must be given to access requirements and the possible need to remove the unit later in the unlikely event of repairs. The unit also requires a 230V socket nearby.



